

	Halocarbon Volume for FM200 @ 6.8%		Inert Volume for IG541 @ 34.5%				
	Flow Rates @ 50pa	Imperial	Metric	Imperial	Metric	Protected Height	Flooded Height
5100	5700 CFM	78,000	2,209	35,000	991	16.8 ft / 5.12 m	20 ft / 6.1 m
6100	7700 CFM	106,000	3,002	47,500	1,345	16.8 ft / 5.12 m	21 ft / 6.4 m
7100 (Drive)	7358 CFM	101,000	2,860	45,000	1,274	16.8 ft / 5.12 m	22 ft / 6.7 m
7100 (Battery)	8413 CFM	115,000	3,256	51,500	1,458	16.8 ft / 5.12 m	23 ft / 7 m
5200	11400 CFM	156,000	4,417	70000	1,982	16.8 ft / 5.12 m	24 ft / 7.3 m
6200	15400 CFM	212,000	6,003	95,000	2,690	16.8 ft / 5.12 m	25 ft / 7.6 m
7200 (Drive)	14716 CFM	202,000	5,720	90,000	2,549	16.8 ft / 5.12 m	26 ft / 7.9 m
7200 (Battery)	16826 CFM	230,000	6,513	103000	2,917	16.8 ft / 5.12 m	27 ft / 8.2 m
300	783 CFM	11,000	312	5,000	142	16.8 ft / 5.12 m	20 ft / 6.1 m